



Venture Tape

30 Commerce Road
Rockland, MA 02370-0384

17/10/2007
781-871-1400
Fax: 781-871-0065

1517CW

1.2 MIL (30 MICRON) ALUMINUM FOILTAPE

DESCRIPTION: A high strength 1.2 mil (30 micron) aluminum foil tape coated with Venture's "CW" cold weather acrylic adhesive system. This adhesive combines high quick stick at low, normal and high temperatures along with excellent long-term performance at low temperatures and high humidity environments.

APPLICATIONS: Primarily used as a vapor sealing tape for foil faced insulation Products in the Industrial, H&V , and Structural Insulation Industry.

TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
Thickness: (exclusive of liner)	2.6 mils (.0026")	0.066 mm
Adhesion:		
Peel:	80 oz/inch width	22.6 N/2.5 cm
Shear: 96+ hrs @	2.2 psi	15.2 kPa
Tensile:	18 lbs/inch width	81.5 N/2.5 cm
Elongation:	5%	5%
Low Temperature Application:	-10°F	-23°C
High Temperature Resistance:	250°F	121°C
Low Environmental Resistance:	-48°F	-44°C
Conforms to British Standard BS 476: Part 7, Class 1; Part 6, Class 0. Lloyds Approved for Marine Applications.	Lloyds Certificate No. Mod B No.	SAS F050388 MED0550314
Conforms to German Standard DIN A-2 Coast Guard Approval No: 164.012/139/0 U.L. FILE NO.: R10984 Underwriters Laboratories Registered Trademark		
Flame Spread:	5	Smoke Developed: 10

IMPORTANT INFORMATION:

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 9/23/97