



30 Commerce Road  
Rockland, MA 02370

Phone: 1-800-343-1076  
Fax: 781-871-0065

## Technical Data Sheet

**Product No.:** 1580      **Duct Sealing Tape**  
**Description:** 1580 is a pressure sensitive duct joint sealer and general purpose sealer on a roll. 1580 provides an instant water resistant bond to most surfaces including sheet metal, duct board, flex duct, and duct wrap vapor barriers. 1580 stays flexible and resists releasing.  
**Applications:** Indoor and outdoor duct sealing tape

	Technical Data	
	Imperial	Metric
<b>Adhesive thickness:</b>	15.0 mil (0.0150")	0.3810 mm
<b>Substrate Thickness:</b>	2.0 mil (0.0020")	0.0508 mm
<b>Peel Adhesion (PSTC-1):</b>	160 oz/inch	45.3 N/2.5 cm
<b>Tensile (PSTC-31):</b>	27 lbs/inch width	122 N/2.5 cm
<b>Elongation:</b>	5 %	5%
<b>Maximum continuous use Temperature:</b>	220°F	104°C
<b>Minimum application temperature:</b>	35°F	1.7°C
<b>Release Liner:</b>	2.7 mil	67.5 micron
	White poly liner	

The information listed is in good faith and has been established from sources believed to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities.