

DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY**1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Trade name	:	DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY		
Company	:	Dow Corning S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium		
Service	:	Dow Corning Central Europe	Tel: +49 6112371	
			Fax: +49 611237609	
		Dow Corning Northern Europe	Tel: +44 1676528000	
			Fax: +44 1676528001	
		Dow Corning Southern Europe	Tel: +33 472841360	
			Fax: +33 472841379	
Emergency Phone Number	:	Dow Corning (Barry U.K. 24h)	Tel: +44 1446732350	
		Dow Corning (Wiesbaden 24h)	Tel: +49 61122158	
		Dow Corning (Seneffe 24h)	Tel: +32 64 888240	
Use of the substance/preparation	:	Construction materials and additives		

2. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone elastomer

Hazardous Ingredients:

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Trimethoxy(methyl)silane	1185-55-3	214-685-0	2.0	F Xn	R11 R22

3. HAZARDS IDENTIFICATION

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

4. FIRST AID MEASURES

On contact with eyes	:	Flush with water.
On skin contact	:	Flush with water. Wipe off.
If inhaled	:	Remove to fresh air.
On ingestion	:	No first aid should be needed.

5. FIRE FIGHTING MEASURES

DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY

Suitable extinguishing media	:	Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.
Unsuitable extinguishing media	:	None known.
Hazards during fire fighting	:	None known.
Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.
Hazardous Combustion Products	:	Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	:	Wear proper protective equipment.
Precautions to protect the environment	:	Do not allow large quantities to enter drains or surface waters.
Methods for cleaning up	:	Scrape up and place in a container fitted with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE

Advice on safe handling	:	General ventilation is recommended. Local ventilation is recommended. Avoid skin and eye contact. Do not breathe vapour.
Advice on storage	:	Do not store with oxidizing agents. Keep container closed and store away from water or moisture.
Specific uses	:	Refer to technical data sheet available on request.
Unsuitable packaging materials	:	None known.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls : Ventilation : Refer to Section 7

Exposure controls for hazardous components

Name	CAS-No.	Exposure Limits
Trimethoxy(methyl)silane	1185-55-3	200 ppm TWA, 250 ppm STEL as methanol

Personal protection equipment

DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY

Hazardous decomposition products : See section 11.

11. TOXICOLOGICAL INFORMATION

On contact with eyes : May cause temporary discomfort.

On skin contact : May produce an allergic reaction.

If inhaled : Vapours evolved during curing may cause dizziness.

On ingestion : Small amounts transferred to the mouth by fingers during use should not injure. Swallowing large amounts may cause digestive discomfort.

Other Health Hazard Information : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form.

¹ Based on product test data.

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION**Environmental fate and distribution**

Solid material, insoluble in water. No adverse effects are predicted.

Ecotoxicity effects

No adverse effects on aquatic organisms are predicted.

Bioaccumulation : No bioaccumulation potential.

Fate and effects in waste water treatment plants

No adverse effects on bacteria are predicted.

13. DISPOSAL CONSIDERATIONS

Product disposal : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Packaging disposal : Dispose of in accordance with local regulations. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION**Road / Rail (ADR/RID)**

DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION**Labelling according to EEC Directive**

S-phrases : S24 Avoid contact with skin.
S51 Use only in well-ventilated areas.

Other phrases : Contains N-(3-(Trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction.

National legislation / regulations

Ozone depleting chemicals : No ozone depleting chemicals are present or used in manufacture.

Status

EINECS : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

DOW CORNING(R) 791 WEATHERPROOFING SEALANT GREY**16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

R11 Highly flammable., **R22** Harmful if swallowed.