



# Venture Tape

30 Commerce Road  
Rockland, MA 02370-0384

08/11/2007  
781-871-1400  
Fax: 781-871-0065

## 923

### CLEAR REMOVABLE POLYETHYLENE TAPE

**DESCRIPTION:** A 5 mil (125 micron) thin, strong and conformable clear polyethylene film tape coated with a specially formulated, high tack, removable acrylic non-curing adhesive system. Excellent ultra violet resistance and resistance to moisture, acids, chemicals, alkalis, oils, abrasion, and weathering.

**APPLICATIONS:** Used as a weather seal for applying plastic storm windows, film can sealing, ink container sealing, and poly sheeting where adhesive removability is desired. Surface protection of glazed and printed surfaces.

#### TECHNICAL DATA

	<u>IMPERIAL</u>	<u>METRIC</u>
<b>Thickness:</b>	6.25 mil (.00625")	0.157mm
<b>Adhesion:</b>		
<b>Peel (PSTC #1)</b>	24.0 oz/inch width	6.8 N/2.5cm
<b>Shear (PSTC #7)</b>	min 4+hrs @ 2psi	13.8kPa
<b>Tensile:</b>	12.5 lb/inch width	56.6 N/2.5cm
<b>Elongation:</b>	250%	250%
<b>Low Temperature Application:</b>	30°F	-1°C
<b>High Temperature Resistance:</b>	175°F	80°C

#### **IMPORTANT INFORMATION:**

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties and are not intended to be used as specifications for defined applications. User must determine the product suitability for the end use application and assume all risks and liabilities. 5/14/99