

SAFETY DATA SHEET

Crown™, Icerock®, Paroc, Rocksilks™, Loft Roll™, Thermolan™ Krimpack™

<p>1. IDENTIFICATION</p> <p>Mineral Wool (glass wool and/or rock wool) for thermal and/or acoustic insulation. For use in building construction</p>	<p>2. COMPOSITION</p> <p>Inert vitreous silicate mineral wool (>18% alkali and earth alkali oxides) Xi: R38. Up to 5.5% of cured thermosetting phenolic resin which has been urea extended. Up to 0.9% of mineral oil.</p>
<p>3. HAZARD IDENTIFICATION</p> <p>May cause temporary (but reversible) skin irritation by mechanical action. Cutting and handling may create dust. High dust levels may irritate the throat or eyes. The resin poses no known hazard in its cured state.</p>	<p>4. FIRST AID MEASURES</p> <p>EYES: If irritation occurs wash eyes with water. SKIN: If irritation occurs, wash skin with soap and water. INHALATION: Move person to fresh air INGESTION: Drink plenty of water if accidentally ingested. If any adverse reaction or discomfort continues from any of the above exposures, seek medical advice.</p>
<p>5. FIRE FIGHTING MEASURES</p> <p>The products do not pose a fire hazard. However, some packaging materials or facings may burn.</p> <p>a) Suitable Extinguishing Media - water, foam, carbon dioxide or dry powder. b) Products of combustion - carbon dioxide, carbon monoxide and some trace gases.</p>	<p>6. ACCIDENTAL RELEASE MEASURES</p> <p>Large pieces may be placed in plastic bags or waste bins. Granules or dust should be collected using vacuum cleaning or by damping down with water spray prior to brushing up. Minimise exposure to dust. See section 8 for recommended personal protection measures.</p>
<p>7. HANDLING AND STORAGE</p> <p>Avoid unnecessary handling of unwrapped product. Store in original packaging in a dry place.</p> <p>If cutting material use sharp hand tools and avoid power tools.</p> <p>Ensure adequate ventilation of workspaces.</p> <p>Keep work areas clean. Use water sprays to dampen area prior to brushing, or use vacuum cleaning.</p>	<p>8. EXPOSURE CONTROLS - PERSONAL PROTECTION</p> <p>MEL - Airborne dust: 5 mg/m³, 8 hour TWA (gravimetric method). For product used in its intended application and with account taken of the guidance given in this document, it is unlikely that this limit will be exceeded. Respiratory protection: In confined spaces it is recommended that disposable face masks complying with EN149 FFP1 or FFP2 should be used and are suitable for most applications to improve comfort. Hand protection: Cloth, leather or rubber gloves can be worn to reduce any mechanical irritation affects which may occur, but see section 15. Eye protection: When working with product above head height, eye protection to BS EN 166 is advised. Skin protection: Loose fitting clothing is advised.</p>
<p>9. PHYSICAL & CHEMICAL PROPERTIES</p> <p>Appearance - Vitreous mineral wool supplied as rolls, slabs or in sectional form, with or without facings. Melting point - Above 600°C. Solubility - Insoluble in water and generally chemically inert.</p>	<p>10. STABILITY AND REACTIVITY</p> <p>No special physical conditions need to be avoided. No restrictions regarding incompatible materials. Binder will decompose above 230°C. Decomposition products principally Carbon Dioxide, Carbon Monoxide and some trace gases, but do not constitute a hazard in normal ventilated areas.</p>
<p>11. TOXICOLOGICAL INFORMATION</p> <p>Not classified as a carcinogen under the EU Dangerous Substances Directive 67/548/EEC and Directive 97/69/EC. No link between exposure to mineral wool fibres and lung disease in production or user industries. IARC Group 3 (not classifiable) No adverse irritant reaction to skin in dermal patch tests No chronic effects usually associated with skin or eye contact</p>	<p>12. ECOLOGICAL INFORMATION</p> <p>Inert inorganic product with very small organic content < 5.5% If disposed in landfill it will gradually decompose and revert to natural Inorganic granules or dust with no known adverse environmental impact. May be used for soil conditioning in heavy soils. No impact upon food chain</p>
<p>13. DISPOSAL CONSIDERATIONS</p> <p>No special precautions. Not classified as Hazardous waste. European waste catalogue code 17 06 04</p>	<p>14. TRANSPORT INFORMATION</p> <p>Not classified for transport</p>
<p>15. REGULATORY INFORMATION</p> <p>Skin irritant (R38) according to Directives 67/548/EEC and 97/69/EC. S 36/37 Wear suitable protective clothing and gloves. COSHH Regulations - Schedule 1: MEL of 5 mg/m³ dust, 8 hour TWA (gravimetric) applies to all mineral wool dust.</p>	<p>16. OTHER INFORMATION</p> <p>Xi:R38 Irritant to the skin Eurisol Health Statement – Eurisol UK Ltd, P.O. box 35084, London. NW1 4XE HSE Guidance Note EH40: Occupational Exposure Limits. This data sheet does not constitute a workplace risk assessment for COSHH.</p>

This Material Safety Data Sheet is in accordance with the EU Directive 91/155/EEC, amended by 93/112/EC and 2001/58/EC.

Assessment according to EU Directive 97/69/EC on MMVF and CHIP3.

Revised Dec 2005 - product name change, EH46 reference removed

Date of previous revisions: 14 December 1998, and 25 August 2000. May 2002, Jan 2003, July 2004, Sept 2005