

HAZARD DATA SHEET

This data sheet provides general safety information and supplements the information which the supplier has a duty to provide under C.O.S.H.H. 1988 and section 6 of the Health and Safety at Work Act 1974 as amended by the Consumer Protection Act 1987. The supplies information must set out the conditions necessary to ensure that the substance is safe and without risk to health when it is being used, handled, processed, stored, transported and on disposal.

PRODUCT													
PRODUCT:	RIGID POLYISOCYANURATE (PIR) FOAM LAMINATE												
PRODUCT NAME:	ECOTHERM ECO-METRE												
DESCRIPTION OF PRODUCT:	RIGID PIR CORE FACED WITH BITUMEN COATED GLASS TISSUE ON ONE SIDE AND BITUMEN COATED GLASS TISSUE WITH POLYPROPYLENE FLEECE ON THE OTHER												
PRODUCT USE:	TORCH ON (FULLY AND PARTIALLY BONDED) OR ROLL AND POUR (FULLY AND PARTIALLY BONDED) ASPHALT AND SINGLE PLY BITUMINOUS SYSTEMS												
PACKAGING:	SHRINK WRAPPED, VARIABLE IN QUANTITY DEPENDING ON THE THICKNESS OF BOARD, PALLETISED												
STORAGE:	STORE BOARDS INDOORS IN A FLAT, DRY AREA OFF THE GROUND AND AWAY FROM MECHANICAL DAMAGE AND SOURCES OF IGNITION. IF TEMPORARY OUTDOOR STORAGE CANNOT BE AVOIDED, BOARDS SHOULD BE COMPLETELY COVERED WITH WEATHER PROOF SHEETING.												
HAZARDS													
HAZARDOUS REACTIONS:	NONE												
DECOMPOSITION:	THERMAL DECOMPOSITION AND BURNING MAY RELEASE CARBON DIOXIDES AND OTHER TOXIC GASES AND VAPOURS												
TRANSPORT:	NON-HAZARDOUS												
PRECAUTIONS:	WHEN CUTTING, WEAR EYE PROTECTION, GLOVES AND MASK												
PERSONAL PROTECTION:	PROTECTIVE CLOTHING, GLOVES, EYE PROTECTION AND DUST MASK												
FIRST AID:	<table style="width: 100%; border: none;"> <tr> <td style="width: 15%;">EYES</td> <td>WASH WITH COPIOUS AMOUNTS OF WATER</td> </tr> <tr> <td>SKIN</td> <td>NORMAL HYGIENE PROCEDURES, WASH AFTER USE</td> </tr> <tr> <td>INHALATION</td> <td>IF INHALATION OF LARGE QUANTITIES OF DUST SHOULD OCCUR, REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION</td> </tr> <tr> <td>INGESTION</td> <td>NO HAZARDS KNOWN</td> </tr> </table>	EYES	WASH WITH COPIOUS AMOUNTS OF WATER	SKIN	NORMAL HYGIENE PROCEDURES, WASH AFTER USE	INHALATION	IF INHALATION OF LARGE QUANTITIES OF DUST SHOULD OCCUR, REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION	INGESTION	NO HAZARDS KNOWN				
EYES	WASH WITH COPIOUS AMOUNTS OF WATER												
SKIN	NORMAL HYGIENE PROCEDURES, WASH AFTER USE												
INHALATION	IF INHALATION OF LARGE QUANTITIES OF DUST SHOULD OCCUR, REMOVE TO FRESH AIR AND SEEK MEDICAL ATTENTION												
INGESTION	NO HAZARDS KNOWN												
FIRE													
FIRE:	IGNITION TEMPERATURE: 450° CENTIGRADE (APPROX.)												
FIRE ACTION:	IF FIRE GETS OUT OF HAND, CALL FIRE BRIGADE AND SHOW THEM THIS LEAFLET												
FIRE EXTINGUISHERS:	<table style="width: 100%; border: none;"> <tr> <td style="text-align: center;">DRY POWDER</td> <td style="text-align: center;">WATER</td> <td style="text-align: center;">FOAM</td> <td style="text-align: center;">CO₂</td> </tr> <tr> <td style="text-align: center;">✓</td> <td style="text-align: center;">✓</td> <td style="text-align: center;">✓</td> <td style="text-align: center;">✓</td> </tr> </table>	DRY POWDER	WATER	FOAM	CO ₂	✓	✓	✓	✓				
DRY POWDER	WATER	FOAM	CO ₂										
✓	✓	✓	✓										
WASTE DISPOSAL:	CONSULT LOCAL AUTHORITY												
TECHNICAL INFORMATION:	<table style="width: 100%; border: none;"> <tr> <td style="width: 30%;">SIZE</td> <td>834 X 1200 MM</td> </tr> <tr> <td>FOAM DENSITY</td> <td>31 KG/M³</td> </tr> <tr> <td>COMPRESSIVE STRENGTH</td> <td>150KPA</td> </tr> <tr> <td>THERMAL CONDUCTIVITY</td> <td>25 to 79mm = 0.026 W/mK</td> </tr> <tr> <td></td> <td>80 to 119mm = 0.025 W/mK</td> </tr> <tr> <td></td> <td>120 to 200mm = 0.024 W/mK</td> </tr> </table>	SIZE	834 X 1200 MM	FOAM DENSITY	31 KG/M ³	COMPRESSIVE STRENGTH	150KPA	THERMAL CONDUCTIVITY	25 to 79mm = 0.026 W/mK		80 to 119mm = 0.025 W/mK		120 to 200mm = 0.024 W/mK
SIZE	834 X 1200 MM												
FOAM DENSITY	31 KG/M ³												
COMPRESSIVE STRENGTH	150KPA												
THERMAL CONDUCTIVITY	25 to 79mm = 0.026 W/mK												
	80 to 119mm = 0.025 W/mK												
	120 to 200mm = 0.024 W/mK												