


Other Standard Ancon Wall Ties

lengths shown in *red italics* refer to items available within 24 hours


RT3

Lengths *200, 225, 250mm*
Conforms to BS5628-1 as a Type 3 tie



SDB


Lengths *125, 150, 175, 200, 225mm*



DT Double Triangle


Lengths *150*, 200*, 225*, 250**, 300mm***

*Conforms to BS5628-1 as a Type 2 tie
**Type 3 tie




SDV

Lengths *125, 150, 175, 200, 225mm*




ACO1 Butterfly

Lengths *200*, 225, 250mm*
*Conformed to BS 1243 (withdrawn in 2005) and suitable for party walls. Ancon recommends use of the HRT4 tie (page 8)




SD21

Lengths *125, 150, 175, 200, 225mm*
For use with 21/18 Omega Channel




SD1

Lengths *200, 225, 250, 275, 300mm*
Conforms to BS5628-1 as a Type 1 tie. Also available with a central drip



WHX

Lengths 150, 175, 200mm




SPS

Lengths *150, 200, 225, 250, 275, 300mm*


SPS CJ

Lengths *150mm*
(3mm thickness for collar-jointed construction)




SRB

Lengths *125, 150, 175, 200mm*



Ancon SPB Frame Cramp




CAN BE USED WITH A DEBONDING SLEEVE

Lengths 75, *100, 125, 150, 175, 200mm*

Application

Safety-ended frame cramp used to join masonry to concrete or steel frames.

Ancon PPS Movement Tie



FOR VERTICAL MOVEMENT JOINTS

Lengths *225, 250mm*

Application

Flat tie used with a debonding sleeve to allow the masonry to expand or contract.