

Masonry biocide

weber CL150

algicide



About this product

weber CL150 is a water-based masonry wash containing carefully selected biocides effective against a broad range of bacterial, fungal, algal, yeast and mould species. It is used as a masonry cleaner and steriliser to kill green, black and other organic growths on walls and other masonry, particularly prior to the application of decorative finishes.

Note: The 25 litre drums of **weber CL150** can be supplied tinted for ease of identification of treated areas. If **weber CL150** is being used to treat finished surfaces, ensure that unpigmented **weber CL150** is specified.

Technical data

Water based solution of chemical biocides approved by Health and Safety Executive and by Dept. of Agriculture for Northern Ireland.

Uses

- Can be used on most interior and exterior surfaces, including brickwork, blockwork, concrete, stone, cement based board, gypsum plaster, timber and previously decorated surfaces
- Suitable for use in the preparation of surfaces where the **Weber** range of renders and decorative finishes are to be applied

Features and benefits

- ▲ Fast acting
- ▲ Simple application
- ▲ Established track record in varying climatic conditions
- ▲ Untinted versions show no residue after treatment
- ▲ Ready for use
- ▲ 25-litre tinted version for easy identification of coated areas

weber CL150

Preparation

Organic growths may indicate consistently damp conditions. Sources of moisture should be identified and rectified to prevent reoccurrence. Condensation, rising damp, faulty plumbing or guttering, etc. should be considered as possible sources.

Application

As soon as access is available, drench apply **weber CL150** solution onto the wall surfaces ensuring they have already been tested for soundness.

Where existing bossed render is being removed as part of the preparation, **weber CL150** solution should be applied to the affected areas after the defective render has been removed.

weber CL150 is ready for use.

When treating large areas, **weber CL150** is best applied using a pressurised knapsack or garden sprayer but can be brush applied if areas are limited. **weber CL150** must be left for a minimum of 48 hours to take effect and kill the growing moss and unseen spores. Dead growth should be removed by brushing with a stiff bristle or wire brush or alternatively by power washing.

Wear protective clothing and safety equipment.

Do not apply **weber CL150** in rain or in temperatures below 5°C or if exposure to these conditions is likely within 24 hours of application.

Cleaning

All equipment must be cleaned immediately after use with water. Waste material should not be emptied into drainage systems.

Packaging

weber CL150 is supplied ready for use in 5 and 25 litre bottles.
The tinted option is available in 25 litres only.

Coverage

Coverage is approximately 0.1 litre/m².

This will vary considerably depending on the suction of the substrate and method of application.

Storage and shelf life

Store in cool, dry conditions at a temperature greater than 5°C. Protect from sunlight and sources of direct heat. The container should be kept sealed when not in use.
25 litre plastic drums - stack no more than 2 high.
Shelf life of product stored in correct conditions is 12 months.

Health and safety

Contains coco alkyl dimethyl benzyl ammonium chloride.

Harmful in contact with skin and if swallowed.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water. Wear suitable gloves and eye/face protection

For further information, please request the Material Safety Data Sheet for this product.

Technical services

Weber's Customer Services Department has a team of experienced advisors available to provide on-site advice both at the specification stage and during application. Detailed specifications can be provided for specific projects or more general works. Site visits and on-site demonstrations can be arranged on request.

Technical helpline

Tel: (01525) 722110
Fax: (01525) 718988

Sales enquiries

Sales, England and Wales

Tel: (01782) 813028
Fax: (01782) 839028

Sales, Scotland

Tel: (0141) 445 0121
Fax: (0141) 445 0122

Sales, Ireland

Tel: (028) 9335 2999
Fax: (028) 9332 3232

Saint-Gobain Weber Ltd
Dickens House, Enterprise Way, Maulden Road, Flitwick, Bedford MK45 5BY, UK
Tel: 08703 330070 Fax: (01525) 718988 e-mail: mail@netweber.co.uk

To the best of our knowledge and belief, this information is true and accurate, but as conditions of use and any labour involved are beyond our control, the end user must satisfy himself by prior testing that the product is suitable for his specific application, and no responsibility can be accepted, or any warranty given by our Representatives, Agents or Distributors. Products are sold subject to our Standard Conditions of Sale and the end user should ensure that he has consulted our latest literature.