



Data Sheet No: ICO0311

Monofilament 250

Vapour Control Layer

Data Sheets

Monofilament 250 is produced from virgin polyethylene, with a reinforcing grid of high density polyethylene built-in. This process gives Monofilament exceptional strength, and a very high tear and puncture resistance.

TECHNICAL DETAILS	
Size	: 2m x 50m 4m x 50m
Colour	: Clear
Thickness	: 0.25mm
Roll Weight	: 26kg 50kg
Water Vapour Transmission	: $0.4\text{gm}^{-2}\text{ day}^{-1}$
Water Vapour Resistance	: 530 MNsg^{-1}
Thermal Behaviour	: Stable between -40°C and $+75^{\circ}\text{C}$
Tensile Strength	: 5.9 kN/m

NOTE: This information is given in good faith being based on the latest knowledge available to Icopal Limited. Whilst every effort has been made to ensure that the contents of the publication are current while going to press, customers are advised that products, techniques and codes of practice are under constant review and liable to change without notice.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on any information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.

Icopal Limited

Barton Dock Road
Stretford
Manchester
M32 0YL

Telephone 0161 865 4444
Fax 0161 864 2616
www.icopal.co.uk

**WORLD LEADER
IN
WATERPROOFING**