



May 2009

Rafter Roll 32

For pitched roofs at rafter level

Description

Rafter Roll 32 is a semi-rigid roll of glass mineral wool with extra high thermal performance, designed for friction fitting between rafters.

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m ² K/W)	Length (m)	Width (mm)	Area per pack (m ²)
100	0.032	3.10	4.00	1200	4.80
85	0.032	2.65	4.60	1200	5.52
75	0.032	2.30	5.25	1200	6.30
65	0.032	2.00	6.10	1200	7.32
50	0.032	1.55	7.90	1200	9.48

All dimensions are nominal

Performance

Thermal

Rafter Roll 32 has a thermal conductivity of 0.032 W/mK.

Fire

Rafter Roll 32 is classified as Euroclass A1 to BS EN ISO 13501-1.

Acoustics

Rafter Roll 32 has excellent sound absorption characteristics.

Benefits

- Very high thermal performance
- Provides thermal and acoustic performance
- Quick and easy installation
- Friction fitting allows rafter spacing to be completely filled, thus eliminating air gap
- Long roll lengths

Rafter Roll 32

Application

Rafter Roll 32 is designed for insulating between the rafters of pitched roofs in new build and existing buildings. It is easy to cut and friction fit between rafters. Rafter Roll 32 can be used either as a single or double layer between rafters, or as the first layer of a two layer system in combination with Polyfoam Linerboard.

Standards

Rafter Roll 32 is non-combustible glass mineral wool, defined as mineral wool in BS 3533: 1981 and is manufactured in accordance with BSI Quality Assurance Standard BS EN ISO 9001: 2000, and Product Standard EN 13162.

Durability

Rafter Roll 32 is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Vapour resistance - resistivity

Rafter Roll 32 offers negligible resistance to the passage of water vapour and has a vapour resistivity of 7.00 MN.s.g.m.

Environmental

Rafter Roll 32 is free from CFCs, HCFCs and any other material with ozone depletion potential in its manufacture and content and represents no known threat to the environment. **Rafter Roll 32's manufacture has a low impact on the environment and is classified as Zero ODP and Zero GWP.**

Handling and storage

Rafter Roll 32 is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied in polythene packs which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Installation instructions are on every pack. Rafter Roll 32 should not be left permanently exposed to the elements.

Knauf Insulation mineral wool products with ECOSE® Technology benefit from a formaldehyde-free binder made from rapidly renewable bio-based materials instead of petroleum-based chemicals which is up to 70% less energy intensive. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE® Technology contain no dye or artificial colours – the colour is completely natural.

Knauf Insulation Ltd

PO Box 10
Stafford Road
St Helens
Merseyside
WA10 3NS

Customer Service (sales)

Tel: 0844 800 0135

Technical Advisory Centre

Tel: 01744 766 666

Literature

Tel: 08700 668 660

www.knaufinsulation.co.uk